



Declaration of Performance

Nr. SB15-800-02-CPR-14

1	Unique identification code of the product type	Baymer® Spray AL 800 - Desmodur® 44V20L <i>Designation code: PU EN 14315-1 – CCC4-CS(10\Y)200</i>
2	Intended use/es	Thermal insulating products for buildings – Insitu formed sprayed rigid polyurethane foam (PUR)
3	Manufacturer	Bayer MaterialScience BV Korte Groningerweg 1a 9607 PS Foxhol Nederland
4	Authorised representative	Not relevant
5	System/s of AVCP	System 3
6a	Harmonised standard	EN 14315-1:2013
	Notified body/ies	IKOB BKB Ringveste 1 3990 GB Houten Nederland <i>Notified Body No. 0957</i> Belgian building research institute (BBRI) Lombardstraat 42 1000 BRUSSEL Belgium <i>Notified Body No. 1136</i> ÉMI Építésügyi Minőségellenorzo Innovációs Nonprofit Kft. Diószegi út 37. 1113 Budapest Hungary <i>Notified Body nummer : 1415</i>

Declaration of Performance

Nr. SB15-800-02-CPR-14

6b European Assessment Document
European Technical Assessment
Technical Assessment Body
Notified body/ies

Not relevant

7 Declared performance/s

Essential characteristics

Essential characteristics	Performance	Specifications
Reaction to fire	E	EN 13501-1
Water permeability	NPD	EN 1609
Thermal resistance	See performance chart	EN 14315-1:2013
Water vapour permeability	NPD	EN 12086:2013
Compressive strength	CS(10/Y)200	EN 826:2013
Durability of reaction to fire against ageing/degradation	NPD	EN 14315-1:2013
Durability of thermal resistance against ageing/degradation	See performance chart	EN 14315-1:2013
Durability of compressive strength against ageing/degradation	NPD	EN 14315-1:2013
Continuous glowing combustion	No harmonized test method available	EN 14315-1:2013

8 Appropriate Technical Documentation and/or Specific Technical Documentation

Not relevant

Declaration of Performance

Nr. SB15-800-02-CPR-14

Type of facing: None or diffusion open		
Thickness	Declared aged thermal conductivity (λ_D)	Thermal resistance level (R_D)
mm	W/m·K	m ² ·K/W
30	0,026	1,15
35	0,026	1,35
40	0,026	1,55
45	0,026	1,75
50	0,026	1,90
55	0,026	2,10
60	0,026	2,30
65	0,026	2,50
70	0,026	2,70
75	0,026	2,90
80	0,027	2,95
85	0,027	3,15
90	0,027	3,35
95	0,027	3,50
100	0,027	3,70
105	0,027	3,90
110	0,027	4,05
115	0,027	4,25
120	0,026	4,60
125	0,026	4,80
130	0,026	5,00
135	0,026	5,20
140	0,026	5,40
145	0,026	5,60
150	0,026	5,75
155	0,026	5,95
160	0,026	6,15
165	0,026	6,35
170	0,026	6,55
175	0,026	6,75
180	0,026	6,90
185	0,026	7,10
190	0,026	7,30
195	0,026	7,50
200	0,026	7,70

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:


Name and function

Place and date of issue

Signature

Alix Uitham
Marketing & Sales manager

Foxhol
15-01-2015



Ceren Özdilek
R&D manager

Foxhol
15-01-2015



Bayer MaterialScience B.V.
Korte Groningerweg 1a
NL-9607 PS Foxhol